

SAFETY DATA SHEET

PRORESTORE

PRODUCTS

Revision Date 21-May-2015
Version 2

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name Crystal Odor Counteractant Commercial Cherry
Product code LG-F1022

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Deodorizer
Restrictions on use Professional Use Only

1.3 Details of the supplier of the safety data sheet

Supplier Legend Brands
ProRestore Products
15180 Josh Wilson Road
Burlington, WA 98233
800-932-3030

1.4 Emergency telephone number

Emergency telephone number INFOTRAC 1-800-535-5053 (North America)
1-352-323-3500 (International)

2. Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910.1200

| | |
|-----------------------------------|-------------|
| Serious eye damage/eye irritation | Category 2A |
| Carcinogenicity | Category 1A |

2.2 Label elements

Signal Word

Danger

Hazard Statements

Causes serious eye irritation
May cause cancer



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3 Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

2.4 Other information

Not Applicable

Unknown Acute Toxicity

1.05187% of the mixture consists of ingredient(s) of unknown toxicity

3. Composition/Information on Ingredients**Substance**

| Chemical Name | CAS-No | Weight % |
|--|------------|----------|
| BENTONITE | 1302-78-9 | 50 - 60 |
| AMORPHOUS SILICA | 7631-86-9 | 10 - 20 |
| ALUMINUM OXIDE | 1344-28-1 | 5 - 10 |
| Distillates, petroleum, hydrotreated light | 64742-47-8 | 5 - 10 |
| IRON OXIDE | 1309-37-1 | 1 - 5 |
| BENZALDEHYDE | 100-52-7 | 1 - 5 |
| CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND | 14808-60-7 | 1 - 5 |
| CALCIUM OXIDE/LIME | 1305-78-8 | 1 - 5 |
| AMYL ACETATE | 628-63-7 | 1 - 5 |
| monochlorotoluene | 25168-05-2 | 1 - 5 |
| MAGNESIUM OXIDE | 1309-48-4 | < 1 |
| Titanium dioxide | 13463-67-7 | < 1 |

* The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures**4.1 Description of first-aid measures****General advice**

No information available.

Eye contact

In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes. Call a poison control center or doctor for treatment advice. Tilt the head to prevent chemical from transferring to the uncontaminated eye.

Skin contact

Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes.

Inhalation

Move to fresh air. Call a physician or poison control center immediately. If breathing is difficult, give oxygen. If not breathing, give artificial respiration.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Dilute with water or milk. Never give fluids if the victim is unconscious or having convulsions.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms See Section 2.2, Label Elements and/or Section 11, Toxicological effects.

4.3 Recommendations for immediate medical care and/or special treatment

Notes to physician Treat symptomatically.

5. Fire-Fighting Measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing agent suitable for type of surrounding fire Use CO₂, dry chemical, or foam. Water may be unsuitable for extinguishing fires Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Unsuitable Extinguishing Media None.

5.2 Specific hazards arising from the substance or mixture

Special Hazard

None known based on information supplied

Hazardous Combustion Products No information available.

Explosion Data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

5.3 Advice for firefighters

Use personal protective equipment. Wear self contained breathing apparatus for fire fighting if necessary. Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. Thoroughly decontaminate all protective equipment after use. Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. .

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

None required for material as supplied. Dust Deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Nonsparking tools should be used.

Other information

Follow personal protective equipment recommendations found in Section 8. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits. Shut off ignition sources; including electrical equipment and flames. Do not allow the spilled product to enter public drainage systems or open waterways. Do not allow smoking in the area.

6.2 Environmental precautions

See Section 12 for additional Ecological information.

6.3 Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Pick up and transfer to properly labeled containers.

7. Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

In case of insufficient ventilation, wear suitable respiratory equipment. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.

Hygiene measures

It is good practice to avoid contact with the product and/or its vapor, mists or dust by using appropriate protective measures. Wash thoroughly after handling and before eating or drinking.

7.2 Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep in a dry place. Avoid dust formation. Keep container tightly closed. Store away from other materials. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals.

Materials to Avoid

No materials to be especially mentioned.

8. Exposure controls/personal protection**8.1 Occupational Exposure Limits (OEL)**

| Chemical Name | ACGIH TLV | OSHA PEL | British Columbia | Alberta | Quebec | Ontario TWAEV |
|--|---|--|---|---|---|---|
| BENTONITE 1302-78-9 | TWA: 1 mg/m ³ respirable fraction | - | TWA: 1.0 mg/m ³ | | | TWA: 1 mg/m ³ |
| AMORPHOUS SILICA 7631-86-9 | - | TWA: 20 mppcf : (80)/(% SiO ₂) mg/m ³ TWA | | | | |
| ALUMINUM OXIDE 1344-28-1 | TWA: 1 mg/m ³ respirable fraction | TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction | TWA: 1.0 mg/m ³ | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ | TWA: 1 mg/m ³ |
| Distillates, petroleum, hydrotreated light 64742-47-8 | - | - | TWA: 200 mg/m ³ Skin | | | |
| IRON OXIDE 1309-37-1 | TWA: 5 mg/m ³ respirable fraction | TWA: 10 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction | TWA: 10 mg/m ³ TWA: 3 mg/m ³ TWA: 5 mg/m ³ STEL: 10 mg/m ³ | TWA: 5 mg/m ³ | TWA: 5 mg/m ³ TWA: 10 mg/m ³ | TWA: 5 mg/m ³ |
| BENZALDEHYDE 100-52-7 | - | - | | | | STEL: 4 ppm STEL: 17 mg/m ³ |
| CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND 14808-60-7 | TWA: 0.025 mg/m ³ respirable fraction | : (30)/(%SiO ₂ + 2) mg/m ³ TWA total dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction | TWA: 0.025 mg/m ³ | TWA: 0.025 mg/m ³ | TWA: 0.1 mg/m ³ | TWA: 0.10 mg/m ³ |
| CALCIUM OXIDE/LIME 1305-78-8 | TWA: 2 mg/m ³ | TWA: 5 mg/m ³ | TWA: 2 mg/m ³ | TWA: 2 mg/m ³ | TWA: 2 mg/m ³ | TWA: 2 mg/m ³ |
| AMYL ACETATE 628-63-7 | STEL: 100 ppm TWA: 50 ppm | TWA: 100 ppm TWA: 525 mg/m ³ | TWA: 50 ppm STEL: 100 ppm | TWA: 50 ppm TWA: 266 mg/m ³ STEL: 100 ppm STEL: 532 mg/m ³ | TWA: 50 ppm TWA: 266 mg/m ³ STEL: 100 ppm STEL: 532 mg/m ³ | TWA: 50 ppm STEL: 100 ppm |

| | | | | | | |
|--------------------------------|---|---|---|---------------------------|---------------------------|---------------------------|
| MAGNESIUM OXIDE 1309-48-4 | TWA: 10 mg/m ³ inhalable fraction | TWA: 15 mg/m ³ fume, total particulate | TWA: 10 mg/m ³ TWA: 3 mg/m ³ STEL: 10 mg/m ³ | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ |
| Titanium dioxide 13463-67-7 | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust | TWA: 10 mg/m ³ TWA: 3 mg/m ³ | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ | TWA: 10 mg/m ³ |

8.2 Appropriate engineering controls**Engineering Measures**

In case of inadequate ventilation wear respiratory protection. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

8.3 Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to handling and processing of material.

Skin and body protection

Wear chemical resistant footwear and clothing such as gloves, an apron or a whole body suit as appropriate.

Respiratory protection

If irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. NIOSH/MSHA approved respiratory protection should be worn if exposure is anticipated.

Hygiene measures

See section 7 for more information

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|----------------|--------------------------|
| Physical state | Solid |
| Appearance | crystalline |
| Color | Black and Beige |
| Odor | Cherry |
| Odor Threshold | No information available |

| <u>Property</u> | <u>Values</u> | <u>Remarks • Methods</u> |
|------------------------------|---------------|--------------------------|
| pH | | No information available |
| Melting/freezing point | | No information available |
| Boiling point/boiling range | | No information available |
| Flash Point | | No information available |
| Evaporation rate | | No information available |
| Flammability (solid, gas) | | No information available |
| Flammability Limits in Air | | |
| upper flammability limit | | No information available |
| lower flammability limit | | No information available |
| Vapor pressure | | No information available |
| Vapor density | | No information available |
| Specific Gravity | 2.5 | |
| Water solubility | | No information available |
| Solubility in other solvents | | No information available |
| Partition coefficient | | No information available |
| Autoignition temperature | | No information available |
| Decomposition temperature | | No information available |
| Viscosity, kinematic | | No information available |
| Viscosity, dynamic | | No information available |
| Explosive properties | | No information available |
| Oxidizing Properties | | No information available |

9.2 Other information

Volatile organic compounds (VOC) 8%
content

10. Stability and Reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under normal conditions

10.3 Possibility of hazardous reactions

None under normal processing.

10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

10.5 Incompatible Materials

None known based on information supplied.

10.6 Hazardous Decomposition Products

Not determined.

11. Toxicological Information

11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

Unknown Acute Toxicity 1.05187% of the mixture consists of ingredient(s) of unknown toxicity

| | |
|--------------------|-----------------|
| Oral LD50 | 8,998.00 mg/kg |
| Dermal LD50 | 12,685.00 mg/kg |
| Mist | 118.70 mg/l |

Numerical measures of toxicity: Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|---|---------------------|-------------------------|------------------------|
| BENTONITE 1302-78-9 | 5000 mg/kg (Rat) | - | - |
| AMORPHOUS SILICA 7631-86-9 | 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 2.2 mg/L (Rat) 1 h |
| ALUMINUM OXIDE 1344-28-1 | 5000 mg/kg (Rat) | - | - |
| Distillates, petroleum, hydrotreated light 64742-47-8 | 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | > 5.2 mg/L (Rat) 4 h |
| IRON OXIDE 1309-37-1 | 10000 mg/kg (Rat) | - | - |
| BENZALDEHYDE 100-52-7 | 1292 mg/kg (Rat) | > 1250 mg/kg (Rabbit) | - |
| CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND 14808-60-7 | 500 mg/kg (Rat) | - | - |
| CALCIUM OXIDE/LIME 1305-78-8 | 500 mg/kg (Rat) | - | - |
| Titanium dioxide 13463-67-7 | 10000 mg/kg (Rat) | - | - |

11.2 Information on toxicological effects

Skin corrosion/irritation

Product Information

• No information available

Component Information

• No information available

Eye damage/irritation

Product Information

• No information available

Component Information

• No information available

Respiratory or skin sensitization

Product Information

• No information available

Component Information

• No information available

Germ Cell Mutagenicity

Product Information

• No information available

Component Information

• No information available

Carcinogenicity

- The table below indicates whether each agency has listed any ingredient as a carcinogen

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---|-------|----------|-------|------|
| CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND 14808-60-7 | A2 | Group 1 | Known | |
| Titanium dioxide 13463-67-7 | - | Group 2B | - | |

Reproductive toxicityProduct Information

- No information available

Component Information

- No information available

STOT - single exposure

No information available

STOT - repeated exposure

No information available

Other adverse effectsTarget Organs

- Central nervous system
- Eyes
- Lungs
- Respiratory system
- Skin
- Not determined.

Product Information

- No information available

Component Information

- No information available

Aspiration hazardProduct Information

- No information available

Component Information

- No information available

12. Ecological information**12.1 Toxicity****Ecotoxicity**

No information available

7.80964484 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Ecotoxicity effects

| Chemical Name | Toxicity to algae | Toxicity to fish | Toxicity to daphnia and other aquatic invertebrates |
|---|--|---|---|
| BENTONITE 1302-78-9 | - | LC50: 96 h Oncorhynchus mykiss 19000 mg/L static | - |
| AMORPHOUS SILICA 7631-86-9 | EC50: 72 h Pseudokirchneriella subcapitata 440 mg/L | LC50: 96 h Brachydanio rerio 5000 mg/L static | EC50: 48 h Ceriodaphnia dubia 7600 mg/L |
| Distillates, petroleum, hydrotreated light 64742-47-8 | - | LC50: 96 h Pimephales promelas 45 mg/L flow-through LC50: 96 h Lepomis macrochirus 2.2 mg/L static LC50: 96 h Oncorhynchus | - |

| | | | |
|---------------------------------|---|--|---|
| | | mykiss 2.4 mg/L static | |
| BENZALDEHYDE 100-52-7 | - | LC50: 96 h Oncorhynchus mykiss 10.6 - 11.8 mg/L flow-through LC50: 96 h Oncorhynchus mykiss 12.69 mg/L static LC50: 96 h Lepomis macrochirus 0.8 - 1.44 mg/L flow-through LC50: 96 h Pimephales promelas 6.8 - 8.53 mg/L flow-through LC50: 96 h Lepomis macrochirus 7.5 mg/L static | - |
| CALCIUM OXIDE/LIME 1305-78-8 | - | LC50: 96 h Cyprinus carpio 1070 mg/L static | - |
| AMYL ACETATE 628-63-7 | - | LC50: 96 h Lepomis macrochirus 650 mg/L static | - |

12.2 Persistence and degradability

No information available.

12.3 Bioaccumulative potential

Discharge into the environment must be avoided

| Chemical Name | log Pow |
|--------------------------|---------|
| BENZALDEHYDE 100-52-7 | 1.48 |

12.4 Mobility in soil

No information available.

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1 Waste Disposal Guidance

Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

14. Transport Information

| | |
|-------------|---------------|
| DOT | Not regulated |
| MEX | Not regulated |
| IMDG | Not regulated |
| IATA | Not regulated |

15. Regulatory information

15.1 International Inventories

| | |
|---------------|----------|
| TSCA | Complies |
| DSL | Complies |
| EINECS/ELINCS | - |
| ENCS | - |
| IECSC | - |
| KECL | Complies |

PICCS -
AICS -
NZIoC -

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL - Canadian Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

15.2 U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

| Chemical Name | SARA 313 - Threshold Values % |
|-----------------------------|-------------------------------|
| ALUMINUM OXIDE 1344-28-1 | 1.0 |

15.3 Pesticide Information

Not applicable

15.4 U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

| Chemical Name | California Prop. 65 |
|---|--|
| CRYSTALLINE SILICA (QUARTZ)/ SILICA SAND - 14808-60-7 | Carcinogen |
| Titanium dioxide - 13463-67-7 | Carcinogen |
| Benzene - 71-43-2 | Carcinogen Developmental Male Reproductive |

16. Other information

| | | | | |
|-------------|------------------------|-----------------------|--------------------------|--|
| NFPA | Health Hazard 1 | Flammability 0 | Instability 0 | Physical and chemical hazards * |
| HMIS | Health Hazard 1 | Flammability 0 | Physical Hazard 0 | Personal protection X |

Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)
Ceiling (C)
DOT (Department of Transportation)
EPA (Environmental Protection Agency)
IARC (International Agency for Research on Cancer)
International Air Transport Association (IATA)
International Maritime Dangerous Goods (IMDG)
NIOSH (National Institute for Occupational Safety and Health)
NTP (National Toxicology Program)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
PEL (Permissible Exposure Limit)
Reportable Quantity (RQ)
Skin designation (S*)
STEL (Short Term Exposure Limit)
TLV® (Threshold Limit Value)

TWA (time-weighted average)

Revision Date 21-May-2015

Revision Note

No information available

Disclaimer

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

End of Safety Data Sheet